OELMANN MULTI-CHARGER

Professional portable's operational storage solution

241.0940LX2 241.0940LX4 241.0940LX8 / Viper 660.1000SME900

A modular unified device for operational storage and charging of:

- LX2, LX4*, LX8 and all of the Viper** Series pagers
- SME900 Series smartphones***
- Easy and reliable fixing up to 5 pagers, charging operations are independent
- Up to 5 multi–chargers can be connected in a chain for independent and simultaneous charging of 25 pagers
- The input voltage is transparently transmitted to the "chain" output connector
- Integrated power alarm monitoring relay contacts
- Reliable protection against over-current

- High-quality metal base housing
- Automatic "operational silence" pager mode when it is in the charger, programmable
- Charging mode indication for each pager seat
- High-quality external AC main power supply, DC input power cable, "chain" power cable jumper and wall-mount set available as options

Technical data

- Number of seats: 5
- 9..30V DC input
- XLR 4–pole connectors

- Power down alarm relay contacts
- -10 .. +55°C
- 575x100x90 mm

* LX2 and LX4 are full featured high compact POCSAG pagers ** Viper Series are LX8 POCSAG, TETRA, GSM, WiFi full featured pagers *** SME Series are POCSAG and IOS beacons full featured rugged smartphones





241.0930 241.0940 AC power supply AC power supply cord



DC power cable





241.0960

DC power jumper



241.0980 Wall-mount set





LX4

241.0950







Specifications are subject to change without notice to improve reliability, function or design. For more and latest information visit http://oelmann-elektronik.com

LX8

TETRA

WIFI

PI_MCHGR_05_EN